Description

Method and device for automatically producing simulation programs

5    The present invention relates to a device and method for producing
simulation programs according to the preamble of claim 1 and in
particular for maintaining systems.

Necessary maintenance measures are generally carried out on an
10   event-controlled or time-triggered basis. With event-controlled
maintenance measures, a process component will be replaced or re-
paired if it has failed. In the case of time-triggered maintenance,
on the other hand, maintenance measures are performed at regular
intervals, the aim being to prevent outage of the process facility.
15

Preventive maintenance is of paramount importance especially where
highly complex facilities are concerned: The outage, for instance,
of a production facility can give rise to very high costs. That is
why complex facilities are frequently monitored by sensors and the
20   measurements used to detect a need for maintenance. This typically
entails performing measurements on components of a facility and re-
cording these measurements during the process. Changes in the meas-
urements allow tendencies to be recognized that may necessitate
maintenance measures. For example, pressure may rise in a facility
25   over time, indicating a blocked pipeline, for instance. As further
examples, vibrations may point to a worn bearing and measurements
performed on the phase angle delta in a motor drive may indicate
unfavorable drift. However, not in every facility can individual
components be constantly monitored for wear and the like: Monitor-
30   ing may be uneconomical in the case, for example, of very high
process temperatures or facilities of very compact physical design,
or if individual components are extremely complex.

Process simulation programs are used for engineering and testing
35   facilities and processes. Simulation programs of this type are pro-
duced by specialists and adapted to suit individual needs. It is

accordingly very expensive to produce simulation programs for large facilities or for multi-layer processes.

The object of the present invention is thus to simplify the produc-

5    tion of simulation programs in particular with regard to maintenance measures.

This object is achieved according to the invention by means of a method for producing a simulation program by making available basic

10    program operations and making available process parameters of a real process and automatically linking the basic program operations to the process parameters for initializing the simulation program.

The above object is further achieved by means of a device for simu-

15    lating a system with a storage facility for making available basic program operations and with a control device for simulating a real process on the basis of the basic program operations, and with a read-in device for reading in process parameters of the real process wherein, by means of the control device, the basic program op-

20    erations for a simulation process can be automatically linked to the process parameters for initializing the simulation process.

The simulation model or program can advantageously be automatically derived from the real process by means of the invention. No addi-

25    tional engineering effort will therefore be required if the control of the real facility has already been provided. This will increase the level of user acceptance in terms of employing simulation models, in particular for maintenance purposes.

30    Further advantageous developments of the device according to the invention and of the method according to the invention can be found in the subclaims.

The present invention will now be described in more detail with the

35    aid of the attached drawings, in which

Fig. 1 shows a data flow diagram of a real process and a simulation process running in parallel according to the invention;

Fig. 2 shows a signal flow diagram for alerting and predicting a
5    need for maintenance; and

Fig. 3 shows a signal flowchart for implementing maintenance measures.

10    The exemplary embodiments described below show preferred embodiments of the present invention.

Fig. 1 shows, in its left half, a schematic signal flowchart of a control of a real process and, in its right half, that of a simula-
15    tion process running in parallel. The job control, or what is called a scheduler, serves as a starting point for controlling the real process. A recipe control (batch flexible) is driven with the job data. The recipe control obtains the required recipe(s) from a database, namely recipe management. This drive is suitable for both
20    batch-processing processes (batch) and continuous processes.

Actual facility control or automation takes place in the block in Fig. 1 designated "sequence logic". A separate component between the recipe control and sequence logic coordinates the instructions
25    with regard to semantics.

The sequence logic is associated with several function blocks FB which are responsible for automating individual steps. Via an input/output periphery the sequence logic and function blocks then
30    exchange instructions and measurements with the process components of the real process. A simple production process performed within a simplified facility could serve as an example of a real process. A container is linked to a reactor via a pipe. The reactor contains two generating sets, a mixer, and a heater set. The container is
35    filled with a certain material. During the production process the reactor could first be filled with the material from the container

then heat and mix said material. The relevant process steps are filling, heating, and mixing. Each of these individual process steps or basic operations has its own internal sequence of instruction steps which is implemented in the sequence logic. The process

5    step 'fill' may, for example, comprise the instructions: Check status of cellular wheel sluice, open slide gate, check fill level etc. In a recipe for producing a certain material the individual process steps are precisely specified. Similar to a cooking recipe, the control recipe contains parameters such as process times, proc-

10   ess temperatures etc. A set sequence of process steps is also specified.

The individual process steps are sequenced in the sequence logic and the respective start and end time specified. Facility compo-

15   nents are individually controlled by function modules as directed by the sequence logic.

A corresponding simulation process is shown on the right-hand side of the figure in Fig. 1. Like the real process system, the simula-

20   tion system consists of a coordination module followed by the sequence logic and equipment function modules. The input/output periphery of the real process is simulated by a logical periphery. The real process itself must be simulated, on the one hand, in its components and, on the other hand, in the process flow itself. The

25   components are simulated in what is called an equipment simulation, and the equipment simulation modules are suitably linked together for the process simulation.

The logical periphery and equipment simulation can be generated

30   automatically by a semantics manager from a library of RB categories (reaction modules).

Equipment master data, material master data, and pipeline master data etc. flow into the process simulation. Equipment master data

35   comprises, for example, the diameter of containers, features of valves, pumps etc. Material master data comprises quantities, grain

size distribution etc. of the material used. Lastly, the pipeline master data corresponds to dimensions and other relevant variables of the pipelines used. All the master data can be filed in libraries.

5     The real process is then synchronized with the simulation process. The two processes consequently run in parallel so as to make a direct comparison of the process results possible. It is not necessary here to simulate the entire real process; instead, a particu-

10    larly critical process step, for example, can be simulated which requires, for instance, constant monitoring.

The simulation allows the entire facility and/or major parts of it to be simulated as a virtual facility. Selectively simulating parts

15    of the facility and comparing the relevant virtual and real process steps allow the need for maintenance to be localized to a degree commensurate with the size of the simulation component. For example, critical parts of the facility can be subdivided into finer process steps in order better to localize the need for maintenance.

20    Where non-critical parts of the facility are concerned, several components can be combined both during measuring of the real process and during the simulation. If a fixed deviation or a deviation increasing with time is then detected on the basis of the comparison of the results of process steps in the real and virtual proc-

25    ess, appropriate maintenance measures can be initiated.

The behavior of a facility from a process control viewpoint is examined so that a need for maintenance can be detected in a timely fashion. This means that, for example, the vibrating of a pump is

30    not measured so that conclusions can be drawn about a worn bearing; instead, the flow through the pump is measured and compared with a simulated ideal flow so that the pump's aging can be detected.

In a development of the invention it would also be possible to

35    simulate the behavior of the material which is contained within the facility and being processed. Conclusions could be drawn about the

facility from the simulated and real chemical conversion process.
For example, deviations in a material's physical state, such a vis-
cosity, could indicate a defective cooling device. Equally, differ-
ences between the simulated and measured PH value, for instance,
5    could indicate a defective mixer.

Whether the physical parameters of the material located within the
facility or typical variables of the facility, such as the through-
put rate, are used for diagnostic purposes, is of secondary impor-
10    tance provided the simulation process runs, according to the inven-
tion, in parallel with the real process and individual results of
process steps or overall results of the process as a whole are com-
pared. For the respective comparison it is necessary for the start
and end of each process step being compared to be defined and rec-
15    ognized. Unique indicators for a need for maintenance can also be
determined. For example, unusually long filling times or excessive
heating times can be recognized that deviate from normal facility
operation. These differences do not necessarily result in an outage
of the entire facility or the production of rejects; they may
20    merely indicate that the facility is not running according to the
planned optimum.

Appropriate maintenance measures can be carried out in keeping with
the magnitude of the deviations. Simply a warning can be directed
25    to the maintenance team if there is only a slight difference be-
tween the real and simulated process. In the case of major differ-
ences a fault message can be issued signaling an immediate need for
maintenance.

30    The diagnostic information obtained from parallel running of the
real and simulated process can also be used to optimize the facil-
ity. If, for example, the facility is run using a changed recipe,
the process steps and/or their sequence will also change. The fa-
cility controller or scheduler converts the new recipe into time
35    flows or time slices. In the case of multi-material facilities, for
example, these time slices must be coordinated as a function of the

different materials and facility components. The aim here is to utilize all parts of the facility to optimum capacity. To improve scheduling online, the simulation process can run in parallel with the real process. Optimization can thereby be achieved without the

5   need for the facility to be idle.

In the case of large facilities and multi-layer processes, controlling the real process requires a high level of engineering effort. The simulation model or program is produced automatically so that

10  this engineering effort does not have to be repeated. For this, basic operations made available in the recipe management and job control are automatically linked with each other in the process simulation. To initialize the simulation program the process parameters of the real process are read out by the SFC sequence logic online.

15  This means the simulation program is automatically provided with the process parameters of the real process, resulting in an exact physical and time-related simulation of the real process.

The process simulation is favorably co-controlled by the job con-

20  trol of the real process. It is, however, also possible to provide a separate control for the simulation. Direct linking in control terms to the real process is, however, especially advantageous for automatic engineering.

25  For automatic engineering, a simulation model must furthermore be adapted in data terms to the control of the real process. An accordingly adapted generic simulation model of a basic operation has, for example, a set of parameters consisting of parameter triples. A triple consists of the "material(s)" parameter, which is

30  product-dependent, the "unit" parameter, which defines the respectively used container, and the "job" parameter, which defines the respectively affected amount of material. The parameters are known from the production recipes. The simulation model is then initialized via this set of parameters so that it corresponds to the real

35  process that is running.

As the simulation models of the basic operations required for pro-
duction are independent of the recipes required for production
("generic") and the simulation, including its provisioning with pa-
rameters, is controlled by the process control system, no addi-
5  tional engineering effort is required for the parallel simulation.

The simulation models are produced in principle automatically from
the recipes of the real process. The simulation models can gener-
ally be produced from semantic programs, semantic periphery assign-
10  ments and/or process control engineering documents, which is to say
from information which the virtual facility needs for describing
its components and how these interact. This information is con-
verted for automatic operation into parameterizing and intercon-
necting the virtual facility.

15

As already mentioned, a meaningful comparison between real and
simulated process steps requires precise synchronizing. A precise
starting point must also be specified, which is done by initializ-
ing. As indicated in Fig. 1 by a broken line, initializing of the
20  simulation process can be controlled online by the sequence logic
of the original facility. For example, it is possible to ensure
that a container in the original facility and in the simulation has
in each case a defined fill level at a specific process step in a
specific recipe.

25

The single arrows in Fig. 1 signify signal links or action links,
and the double arrows signify data connections which are necessary
for, for example, parameterizing and engineering.

30  Fig. 2 shows a schematic signal flowchart for obtaining a mainte-
nance request on the basis of the diagnosis resulting from the com-
parison between the real process and simulation process running in
parallel. Explanations of the modules can be found in the table at
the end of the description.

35

Fig. 3 shows a signal flowchart showing further processing of a

maintenance request in a maintenance management system. According to this, service measures are performed if necessary on the basis of information provisioning, material/resource provisioning, maintenance planning, and the maintenance request. Material/resource administration and the budget have an impact here on maintenance planning. The facility model also serves for information provisioning.

Table

| Component | Function | Task |
|---|---|---|
| <u>PLC</u> | Logic in TF | Suppression of follow-up message.<br>Example 1: Outage of the alerting voltage (simultaneously) takes all the messages from the monitoring loop fed by the alerting voltage ("contacts").<br>Example 2: All messages must be suppressed in on-site operation (from a repair counter).<br>Module message<br>Example 1: Check-back monitoring (protective check-back, rotation speed check-back, operating time message)<br>Example 2: Operating mode changeover |
| | Process data logging | Make process values available that are required for cross-area logic (event-triggered, in the case of measurements for change with dead band) |
| | Logic between TFs | Technological monitoring of a PLT location.<br>Example 1: A jump in setpoint value on a regulator must result a rise in the actual value.<br>Example 2: Manipulated variable of a regulator increases with no change in the setpoint value (wear on valve seating). |

|     |                                                      | Example 3: Pressure or flow measurement on pump group                                                                                                                                                                                                                                |
| --- | ---------------------------------------------------- | ----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------- |
|     | Usage-dependent maintenance                          | Operating cycle/operating time counter<br>Count the operating hours or operating cycles, generate IH request if a parameterized threshold is exceeded                                                                                                                                |
|     | Section chain monitoring                             | Time monitoring for indexing condition                                                                                                                                                                                                                                              |
| PDM | Scan field devices                                   | Information from intelligent field devices<br>PDM (AMS) scans the accessible field devices and transfers messages (selected by parameterizing)<br>Live monitoring of intelligent field devices<br>PDM (AMS) scans the planned field devices and generates a message if a planned device cannot be accessed. |
|     | Should be/as is comparison<br>Project                | Comparison planning –<br>as is<br>PDM (AMS) scans the accessible field devices and generates a message if planning is not as is (read field device not in the project).                                                                                                               |
| CBA |                                                      |                                                                                                                                                                                                                                                                                     |
| CM  | Condition monitoring                                 | Example 1: Vibration monitoring on machine<br>Example 2: Electrical fingerprint for motor<br>Example 3: HISS (smell, hear, taste)                                                                                                                                                   |

| HMI | Operation of operating or recipe parameters | Example: "Standard deviation" parameter for fault message dependent on operating mode |
| --- | --- | --- |
| | Alarms | Planned alarms = IH request |
| Diag | Facility behavior | Comparison of current facility behavior with history. Example 1: How long has it taken so far to bring material x in unit y from m to n fill height? Comparison with current step. IH request via user action with GUI support. User generates IH request Necessary: Facility behavior archive or (at least) parameterized comparison values |
| | Logic between TFs | Technological monitoring of part of a facility Logic or rules on a cross-area basis over several PLT locations (on several PLCs, where applicable) |
| | Diagnostic message | Message frequency Example 1: Specific report numbers from a specific TP are (interactively) "set to diagnosis" and continuously monitored from then on until a suspected fault cause has been recognized/analyzed. Example 1: Suspicion of increased outage rate of a motor drive: The report numbers, protective check-back, and bi- |

| | | |
|---|---|---|
| | | metal message generate a diagnostic message if more than 5 messages occurred per shift. |
| | Simulation evaluation | Compare the result of process-/equipment simulation with real process/facility results. Decision rules specifying when a comparison between simulation result and as-is facility is ok/not ok and (in the case of process simulation) assignment to asset. |
| | Behavior evaluation | Compare value from facility behavior archive or from facility behavior (with fixed values determined in IBS/trial operation) with real facility results. Otherwise as above.<br><br>Note:<br>Simulation evaluation is advantageous in the case of multi-purpose facilities where a meaningful facility behavior archive is not ensured on account of the multiplicity of products/recipes.<br>Behavior evaluation is advantageous in the case of "single-purpose" facilities and conti/semiconti facilities. |
| <u>Sim</u> | Process simulation | Technological monitoring of recipe steps SIMIT has models of the facility Gos (mix, heat, fill etc.). Each individual model |

| | | has parameters (material, unit, and product parameters). The simulation runs under BF control (BF gives the step start, with the parameter set valid for the step and the end criterion (e.g. final tempera-ture 92°C), to SIMIT. SIMIT starts simulation and, on at-tainment of the end criterion, gives the result parameter set defined for the GO to Diag. SIMIT has (as yet) no command of material conversions; op-erations of this type (e.g. "reaction", "synthesis") have to be simulated by simple em-pirical equations if a pass is to be made through several Gos in a "simulation chain". No project-specific enginee-ring work is necessary because this method runs under the control of BF. SIMIT "only" needs models that are proc-ess/project neutral. |
|---|---|---|
| | Equipment behavior | Technological monitoring of the equipment behavior SIMIT has models of the (tech-nological) equipment behavior (e.g. resistance heating ele-ment with time behavior, heat transition, heat flow in the material etc.). Otherwise analogous to the above |

| Arch | Facility behavior archive | History of the product- and substance-/material-dependent time behavior of parts of the facility, units, equipment, and also relevant (fixed) parameters.<br><br>Different embodiments for the process industry and discrete (manufacturing) industry:<br>Process industry: Objects are steps in the flow such as filling, heating etc. and equipment (S 88), not the objects of the facility model such as a pump, regulating valve etc.<br>Discrete industry: Objects are the "machines" of the facility model. |
|------|---------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|